





特 性

- 由銅/鎳或錳/銅合金電阻綫制成
- 優越的焊接性能
- 適用於各種類型的電流感應器應用



CSRA, CSRB, CSRC

規格	綫徑 Ød mm	額定電流	溫度系數	阻值範圍 ±1%, ±5%	備注
CSRA	0.4	2.0A	±100PPM	80mΩ-200mΩ	綫徑如本表所示, P值和H值可根據客戶的要求進行設計
	0.5	2.5A		60mΩ-150mΩ	
	0.6	3.0A		60mΩ-100mΩ	
	0.7	4.0A		35mΩ-60mΩ	
	0.8	4.5A		5mΩ-50mΩ	
	0.9	5.0A		5mΩ-40mΩ	
	1.0	5.5A		3mΩ-30mΩ	
	1.1	6.0A		3mΩ-20mΩ	
	1.2	7.0A		3mΩ-20mΩ	
	1.3	7.5A		3mΩ-20mΩ	
1.4	8.0A	3mΩ-20mΩ			
1.5	9.0A	3mΩ-20mΩ			
1.6	9.5A	3mΩ-15mΩ			
1.8	11A	3mΩ-10mΩ			
2.0	12A	3mΩ-10mΩ			
2.3	14A	3mΩ-7mΩ			

CSRD (扁綫型)

規格	額定功率	H max (mm)	P max (mm)	溫度系數	阻值範圍 ±1%, ±5%
CSRD	1W	11	5	±20PPM	5mΩ-10mΩ
	3W	25	15		5mΩ-10mΩ
	5W	25	20		5mΩ-10mΩ

訂購方式 ( 例如: CSRC15J45M B 0 0 )

