



VCO Product Specification

Model: VCO790-2300TY **Rev:** A **Date:** 8/10/2009
Customer: RF MICRO DEVICES
Operating Temperature Range: (-35 ° to 85 ° C)

RoHS Compliant

Parameter	Min	Typ	Max	Units	X	Remarks
Frequency Range -	2100	2300	2500	MHz	X	
Tuning Voltage:						
2100 MHz	0.5	1.5		Vdc	X	
2500 MHz		3.9	4.5	Vdc	X	
Tuning Sensitivity:						
2100 MHz	161	215	269	MHz/V	X	
2200 MHz	150	200	250	MHz/V	X	
2300 MHz	144	192	241	MHz/V	X	
2400 MHz	128	171	213	MHz/V	X	
2500 MHz	108	145	181	MHz/V	X	
Output Power -	0	3	6	dBm	X	
Output Phase Noise:						
10 kHz		-90	-84	dBc/Hz		
100 kHz		-112	-106	dBc/Hz	X	
Power Supply -	4.75	5	5.25	Volts	X	
Supply Current -		15	20	mA	X	
Harmonic Suppression:						
2nd Harmonic		-25	-10	dBc	X	
3rd Harmonic		-30	-10	dBc	X	
Spurious (Non-Harmonic) -			-80	dBc		
Frequency Pushing - 4.75-5.25 V		10	25	MHz p-p		
Frequency Pulling - 12 dB RL		12.5	25	MHz p-p		
Tuning Port Capacitance -		68		pF		
Output Impedance -		50		Ω		

Package Information

Package Type:	T (0.5 x 0.5 x 0.156 inches)	Drawing Number:	60035
---------------	------------------------------	-----------------	-------

Comments

X Indicates parameter to be tested 100% in production

RoHS status based on EU Directive 2002/95/EC (at time of this document revision).

The information in this publication is believed to be accurate and reliable. However, no responsibility is assumed by RF Micro Devices, Inc. ("RFMD") for its use, nor for any infringement of patents, or other rights of third parties, resulting from its use. No license is granted by implication or otherwise under any patent or patent rights of RFMD. RFMD reserves the right to change component circuitry, recommended application circuitry and specifications at any time without prior notice.