

Features

- On-state rms current, $I_{T(RMS)}$ 25 A
- Repetitive peak off-state voltage, V_{DRM}/V_{RRM} 600 to 800 V
- Triggering gate current, I_{GT} 40 mA
- Insulated package TO-220AB ins
 - Insulating voltage 2500 V rms
 - UL1557 certified (file ref. E81734)

Description

These standard 25 A SCRs are suitable for general purpose applications.

Using clip assembly technology, they provide a superior performance in surge current capabilities.

TXN625RG is packaged in TO-220AB ins.




Table 1. Device summary

| Order code | Voltage V_{DRM}/V_{RRM} | | Sensitivity I_{GT} | Package |
|----------------|---------------------------|-------|----------------------|--------------------|
| | 600 V | 800 V | | |
| TN2540-600G-TR | Y | | 40 mA | D ² PAK |
| TN2540-800G-TR | | Y | 40 mA | D ² PAK |
| TXN625RG | Y | | 40 mA | TO-220AB ins |
| TYN625RG | Y | | 40 mA | TO-220AB |
| TYN825RG | | Y | 40 mA | TO-220AB |

1 Characteristics

Table 2. Absolute ratings (limiting values)

| Symbol | Parameter | | Value | Unit | |
|--------------------|---|------------------------------|-----------------------|--------------------------------|------------------|
| $I_{T(RMS)}$ | On-state rmscurrent (180 °Conduction angle) | TO-220AB, D ² PAK | $T_c = 100\text{ °C}$ | 25 | A |
| | | TO-220AB ins | $T_c = 83\text{ °C}$ | | |
| $I_{T(AV)}$ | Average on-state current (180 °Conduction angle) | | $T_c = 100\text{ °C}$ | 16 | A |
| I_{TSM} | Non repetitive surge peak on-state current | $t_p = 8.3\text{ ms}$ | $T_j = 25\text{ °C}$ | 314 | A |
| | | $t_p = 10\text{ ms}$ | | 300 | |
| I^2t | I^2t Value for fusing | $t_p = 10\text{ ms}$ | $T_j = 25\text{ °C}$ | 450 | A ² s |
| dI/dt | Critical rate of rise of on-state current $I_G = 2 \times I_{GT}$, $t_r \leq 100\text{ ns}$ | F = 60 Hz | $T_j = 125\text{ °C}$ | 50 | A/ μ s |
| I_{GM} | Peak gate current | $t_p = 20\text{ }\mu$ s | $T_j = 125\text{ °C}$ | 4 | A |
| $P_{G(AV)}$ | Average gate power dissipation | | $T_j = 125\text{ °C}$ | 1 | W |
| T_{stg} T_j | Storage junction temperature range Operating junction temperature range | | | - 40 to + 150 - 40 to + 125 | °C |
| V_{RGM} | Maximum peak reverse gate voltage | | | 5 | V |

Table 3. Electrical Characteristics ($T_j = 25\text{ °C}$, unless otherwise specified)

| Symbol | Test conditions | | Value | Unit | | |
|------------------------|---|-----------------------|-----------------------|------|------------|------------|
| I_{GT} | $V_D = 12\text{ V}$ $R_L = 33\text{ }\Omega$ | MIN. | 4 | mA | | |
| | | MAX. | 40 | | | |
| V_{GT} | | MAX. | 1.3 | V | | |
| V_{GD} | $V_D = V_{DRM}$ $R_L = 3.3\text{ k}\Omega$ | $T_j = 125\text{ °C}$ | MIN. | 0.2 | V | |
| I_H | $I_T = 500\text{ mA}$ Gate open | | MAX. | 50 | mA | |
| I_L | $I_G = 1.2 \times I_{GT}$ | | MAX. | 90 | mA | |
| dV/dt | $V_D = 67\% V_{DRM}$ Gate open | $T_j = 125\text{ °C}$ | MIN. | 1000 | V/ μ s | |
| V_{TM} | $I_{TM} = 50\text{ A}$ $t_p = 380\text{ }\mu$ s | $T_j = 25\text{ °C}$ | MAX. | 1.6 | V | |
| V_{t0} | Threshold voltage | | $T_j = 125\text{ °C}$ | MAX. | 0.77 | V |
| R_d | Dynamic resistance | | $T_j = 125\text{ °C}$ | MAX. | 14 | m Ω |
| I_{DRM} I_{RRM} | $V_{DRM} = V_{RRM}$ | $T_j = 25\text{ °C}$ | MAX. | 5 | μ A | |
| | | $T_j = 125\text{ °C}$ | | 4 | mA | |

Table 4. Thermal resistances

| Symbol | Parameter | | Value | Unit | |
|---------------|--------------------------|------------------------------|------------------------|------|------|
| $R_{th(j-c)}$ | Junction to case (DC) | D ² PAK, TO-220AB | 1.0 | °C/W | |
| | | TO-220AB ins | 2.0 | | |
| $R_{th(j-a)}$ | Junction to ambient (DC) | $S^{(1)} = 1 \text{ cm}^2$ | D ² PAK | 45 | °C/W |
| | | | TO-220AB, TO-220AB ins | 60 | |

1. S = Copper surface under tab.

Figure 1. Maximum average power dissipation versus average on-state current




Figure 2. Average and DC on-state current versus case temperature




Figure 3. Average and DC on-state current versus ambient temperature




Figure 4. Relative variation of thermal impedance versus pulse duration (D²PAK, and TO-220AB)




Figure 5. Relative variation of thermal impedance versus pulse duration (TO-220AB ins)




Figure 6. Relative variation of gate trigger, holding, and latching currents versus junction temperature




Figure 7. Surge peak on-state current versus number of cycles




Figure 8. Non-repetitive surge peak on-state current, and corresponding values of I²t




Figure 9. On-state characteristics (maximum values)





Figure 10. Thermal resistance junction to ambient versus copper surface under tab (D²PAK)



2 Ordering information schemes

Figure 11. TN2540-x00G ordering information scheme




Figure 12. TXN625RG ordering information scheme





Figure 13. TYNx25RG ordering information scheme



3 Package information

- Epoxy meets UL94, V0
- Lead-free package
- Recommended torque values (TO-220AB, and TO220AB ins): 0.4 to 0.6 N·m

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK® packages, depending on their level of environmental compliance. ECOPACK® specifications, grade definitions and product status are available at: www.st.com. ECOPACK® is an ST trademark.

Table 5. D²PAK dimensions

| Ref. | Dimensions | | | | | |
|------|-------------|------|-------|--------|-------|-------|
| | Millimeters | | | Inches | | |
| | Min. | Typ. | Max. | Min. | Typ. | Max. |
| A | 4.30 | | 4.60 | 0.169 | | 0.181 |
| A1 | 2.49 | | 2.69 | 0.098 | | 0.106 |
| A2 | 0.03 | | 0.23 | 0.001 | | 0.009 |
| B | 0.70 | | 0.93 | 0.027 | | 0.037 |
| B2 | 1.25 | 1.40 | | 0.048 | 0.055 | |
| C | 0.45 | | 0.60 | 0.017 | | 0.024 |
| C2 | 1.21 | | 1.36 | 0.047 | | 0.054 |
| D | 8.95 | | 9.35 | 0.352 | | 0.368 |
| E | 10.00 | | 10.28 | 0.393 | | 0.405 |
| G | 4.88 | | 5.28 | 0.192 | | 0.208 |
| L | 15.00 | | 15.85 | 0.590 | | 0.624 |
| L2 | 1.27 | | 1.40 | 0.050 | | 0.055 |
| L3 | 1.40 | | 1.75 | 0.055 | | 0.069 |
| R | 0.40 | | | 0.016 | | |
| V2 | 0° | | 8° | 0° | | 8° |

Figure 14. D²PAK footprint (dimensions in mm)






Table 6. TO-220AB dimensions



| Ref. | Dimensions | | | | | |
|------|-------------|-------|-------|--------|-------|-------|
| | Millimeters | | | Inches | | |
| | Min. | Typ. | Max. | Min. | Typ. | Max. |
| A | 15.20 | | 15.90 | 0.598 | | 0.625 |
| a1 | | 3.75 | | | 0.147 | |
| a2 | 13.00 | | 14.00 | 0.511 | | 0.551 |
| B | 10.00 | | 10.40 | 0.393 | | 0.409 |
| b1 | 0.61 | | 0.88 | 0.024 | | 0.034 |
| b2 | 1.23 | | 1.32 | 0.048 | | 0.051 |
| C | 4.40 | | 4.60 | 0.173 | | 0.181 |
| c1 | 0.49 | | 0.70 | 0.019 | | 0.027 |
| c2 | 2.40 | | 2.72 | 0.094 | | 0.107 |
| e | 2.40 | | 2.70 | 0.094 | | 0.106 |
| F | 6.20 | | 6.60 | 0.244 | | 0.259 |
| ØI | 3.75 | | 3.85 | 0.147 | | 0.151 |
| I4 | 15.80 | 16.40 | 16.80 | 0.622 | 0.646 | 0.661 |
| L | 2.65 | | 2.95 | 0.104 | | 0.116 |
| I2 | 1.14 | | 1.70 | 0.044 | | 0.066 |
| I3 | 1.14 | | 1.70 | 0.044 | | 0.066 |
| M | | 2.60 | | | 0.102 | |

Table 7. TO-220AB ins dimensions



| Ref. | Dimensions | | | | | |
|------|-------------|-------|-------|--------|-------|-------|
| | Millimeters | | | Inches | | |
| | Min. | Typ. | Max. | Min. | Typ. | Max. |
| A | 15.20 | | 15.90 | 0.598 | | 0.625 |
| a1 | | 3.75 | | | 0.147 | |
| a2 | 13.00 | | 14.00 | 0.511 | | 0.551 |
| B | 10.00 | | 10.40 | 0.393 | | 0.409 |
| b1 | 0.61 | | 0.88 | 0.024 | | 0.034 |
| b2 | 1.23 | | 1.32 | 0.048 | | 0.051 |
| C | 4.40 | | 4.60 | 0.173 | | 0.181 |
| c1 | 0.49 | | 0.70 | 0.019 | | 0.027 |
| c2 | 2.40 | | 2.72 | 0.094 | | 0.107 |
| e | 2.40 | | 2.70 | 0.094 | | 0.106 |
| F | 6.20 | | 6.60 | 0.244 | | 0.259 |
| ØI | 3.75 | | 3.85 | 0.147 | | 0.151 |
| l4 | 15.80 | 16.40 | 16.80 | 0.622 | 0.646 | 0.661 |
| L | 2.65 | | 2.95 | 0.104 | | 0.116 |
| l2 | 1.14 | | 1.70 | 0.044 | | 0.066 |
| l3 | 1.14 | | 1.70 | 0.044 | | 0.066 |
| M | | 2.60 | | | 0.102 | |

4 Ordering information

Table 8. Ordering information

| Order code | Voltage | Sensitivity | Marking | Package | Weight | Base qty | Delivery mode |
|----------------|---------|-------------|------------|--------------------|--------|----------|---------------|
| TN2540-600G-TR | 600 V | 40 mA | TN2540600G | D ² PAK | 1.5 g | 1000 | Tape & reel |
| TN2540-800G-TR | 800 V | 40 mA | TN2540800G | D ² PAK | 1.5 g | 1000 | Tape & reel |
| TXN625RG | 600 V | 40 mA | TXN625 | TO-220AB ins | 2.3 g | 50 | Tube |
| TYN625RG | 600 V | 40 mA | TYN625 | TO-220AB | 2.3 g | 50 | Tube |
| TYN825RG | 800 V | 40 mA | TYN825 | TO-220AB | 2.3 g | 50 | Tube |

5 Revision history

Table 9. Document revision history

| Date | Revision | Changes |
|-------------|----------|---|
| Apr-2002 | 4A | Previous update |
| 13-Feb-2006 | 5 | TO-220AB delivery mode changed from bulk to tube. ECOPACK statement added. |
| 17-Jun-2011 | 6 | Added TXN625. |
| 13-Sep-2011 | 7 | Added UL certification in Features . |

Please Read Carefully:

Information in this document is provided solely in connection with ST products. STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, modifications or improvements, to this document, and the products and services described herein at any time, without notice.

All ST products are sold pursuant to ST's terms and conditions of sale.

Purchasers are solely responsible for the choice, selection and use of the ST products and services described herein, and ST assumes no liability whatsoever relating to the choice, selection or use of the ST products and services described herein.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted under this document. If any part of this document refers to any third party products or services it shall not be deemed a license grant by ST for the use of such third party products or services, or any intellectual property contained therein or considered as a warranty covering the use in any manner whatsoever of such third party products or services or any intellectual property contained therein.

UNLESS OTHERWISE SET FORTH IN ST'S TERMS AND CONDITIONS OF SALE ST DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY WITH RESPECT TO THE USE AND/OR SALE OF ST PRODUCTS INCLUDING WITHOUT LIMITATION IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION), OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT.

UNLESS EXPRESSLY APPROVED IN WRITING BY TWO AUTHORIZED ST REPRESENTATIVES, ST PRODUCTS ARE NOT RECOMMENDED, AUTHORIZED OR WARRANTED FOR USE IN MILITARY, AIR CRAFT, SPACE, LIFE SAVING, OR LIFE SUSTAINING APPLICATIONS, NOR IN PRODUCTS OR SYSTEMS WHERE FAILURE OR MALFUNCTION MAY RESULT IN PERSONAL INJURY, DEATH, OR SEVERE PROPERTY OR ENVIRONMENTAL DAMAGE. ST PRODUCTS WHICH ARE NOT SPECIFIED AS "AUTOMOTIVE GRADE" MAY ONLY BE USED IN AUTOMOTIVE APPLICATIONS AT USER'S OWN RISK.

Resale of ST products with provisions different from the statements and/or technical features set forth in this document shall immediately void any warranty granted by ST for the ST product or service described herein and shall not create or extend in any manner whatsoever, any liability of ST.

ST and the ST logo are trademarks or registered trademarks of ST in various countries.

Information in this document supersedes and replaces all information previously supplied.

The ST logo is a registered trademark of STMicroelectronics. All other names are the property of their respective owners.

© 2011 STMicroelectronics - All rights reserved

STMicroelectronics group of companies

Australia - Belgium - Brazil - Canada - China - Czech Republic - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan - Malaysia - Malta - Morocco - Philippines - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States of America

www.st.com