




Features

- For Base Station applications
- Usable bandwidth 18 MHz
- Low loss
- High attenuation
- Single-ended operation
- No impedance matching required for operation at 50 Ω
- Single-ended operation
- Ceramic Surface Mount Package (SMP)
- Hermetic
- RoHS compliant (2002/95/EC), Pb-free 




Package

Surface Mount 3.00 x 3.00 x 1.22 mm
SMP-12



Pin Configuration

Bottom View



Pin No.	Description
2	Input
5	Output
1,3,4,6	Case Ground

Dimensions shown are nominal in millimeters
All tolerances are ± 0.15 mm except overall
length and width ± 0.10 mm

Body: Al_2O_3 ceramic
Lid: Kovar, Ni plated
Terminations: Au plating 0.5 - 1.0 μ m,
over a 2 - 6 μ m Ni plating

Electrical Specifications ⁽¹⁾

Operating Temperature Range: ⁽²⁾ -40 to +85 °C


Parameter ⁽³⁾	Minimum	Typical ⁽⁴⁾	Maximum	Unit
Center Frequency	-	737	-	MHz
Maximum Insertion Loss 728 – 746 MHz	-	1.8	2.25	dB
Lower 3 dB Band Edge ⁽⁵⁾	-	722.3	728	MHz
Upper 3 dB Band Edge ⁽⁵⁾	746	751.8	-	MHz
Absolute Attenuation ⁽⁵⁾				
10 – 700 MHz	40	50	-	dB
700 – 708 MHz	37	46	-	dB
766 – 1500 MHz	40	43	-	dB
1500 – 2000 MHz	30	35	-	dB
Input/Output Return Loss 728 – 746 MHz	10	12.5	-	dB
Source Impedance: (Single-ended) ⁽⁶⁾	-	50	-	Ω
Load Impedance: (Single-ended) ⁽⁶⁾	-	50	-	Ω

Notes:





1. All specifications are based on the TriQuint test circuit shown on below
2. In production, devices will be tested at room temperature to a guardbanded specification to ensure electrical compliance over temperature
3. Electrical margin has been built into the design to account for the variations due to temperature drift and manufacturing tolerances
4. Typical values are based on average measurements at room temperature
5. Relative to Zero dB
6. This is the optimum impedance in order to achieve the performance shown

Test Circuit:


Actual matching values may vary due to PCB layout and parasitics




Typical Performance (at room temperature)



Input Smith Chart




Output Smith Chart



Matching Schematics


Actual matching values may vary due to PCB layout and parasitics

50 Ω
Single-ended
Input




50 Ω
Single-ended
Output

Marking





The date code consists of: day of the current year (Julian, 3 digits), Y = last digit of the year and M = manufacturing site code

PCB Footprint



This footprint represents a recommendation only
Dimensions shown are nominal in millimeters

Tape and Reel



Dimensions shown are nominal in millimeters
Packaging quantity: 5000 units/reel

Maximum Ratings


Parameter	Symbol	Minimum	Maximum	Unit
Operating Temperature Range	T	-40	+85	°C
Storage Temperature Range	T _{stg}	-40	+85	°C
Input Power	P _{in}	-	+20	dBm

Notes:


1. Input Power is targeted for an applied CW modulated RF signal at 55 °C for 125 hours

Important Notes

Warnings

- Electrostatic Sensitive Device (ESD) 
- Avoid ultrasonic exposure

RoHS Compliance

- This product complies with EU directive 2002/95/EC (RoHS) 

Solderability

- Compatible with JESD22-B102, Pb-free process, 260C peak reflow temperature ([see soldering profile](#))

Links to Additional Technical Information

[PCB Layout Tips](#)

[Qualification Flowchart](#)

[Soldering Profile](#)

[S-Parameters](#)

[RoHS Information](#)

[Other Technical Information](#)

TriQuint's liability is limited only to the Surface Acoustic Wave (SAW) component(s) described in this data sheet. TriQuint does not accept any liability for applications, processes, circuits or assemblies, which are implemented using any TriQuint component described in this data sheet.

Contact Information

TriQuint 
SEMICONDUCTOR

PO Box 609501
Orlando, FL 32860-9501
USA

Phone: +1 (407) 886-8860
Fax: +1 (407) 886-7061
Email: info-product@tqs.com
Web: www.triquint.com

Or contact one of our worldwide
Network of [sales offices](#),
[Representatives or distributors](#)