

STM8L-PRIMER STM32-PRIMER STMPRIMER

Raisonance STM32 and STM8 Primers for fun, easy evaluation and development with STM32 and STM8

Data brief

Features

- The versatile EvoPrimer range includes:
 - In-circuit debugging/programming via dedicated USB connection to the host PC
 - Evaluation features including USB connector and MEMs sensor
 - Comprehensive development software
 - Ergonomic design
 - MEMs-based controls
 - Touchscreen TFT display, color LCD
 - Joystick
 - Audio circuit/Jack
 - MEMS accelerometer
 - Li-lon battery with charge management circuit
 - Micro SD Card[™] connector
 - Add-on connector for extension boards with USART, SPI, I2C and analog/digital I/Os
- STM8L ultralow power EvoPrimer features:
 - STM8L152C6 MCU with 32 KB Flash
 - Low power consumption
 - LCD (7-segment)
 - Temperature sensor
 - Solar cells
- STM32F connectivity line EvoPrimer features:
 - STM32F107VC MCU with 256 KB Flash
 - Mini-USB OTG connector
- STM32F performance line EvoPrimer features:
 - STM32F103VG MCU with 1 MB Flash
 - Mini-USB connector
- STM32F high-performance and Digital Signal Processing (DSP) EvoPrimer features:
 - STM32F407IG MCU with 1 MB Flash
 - 1.3 M pixel image sensor
 - 3-axis gyroscope
 - 16 Mbit of SRAM
 - STA529A audio-codec
 - Mini-USB connector (HS, USB 2.0 OTG) and dual CAN connector
- STM32L ultralow power EvoPrimer features:
 - STM32L152VB MCU with128 KB Flash



- LCD (14-segment)
- Temperature and pressure sensors
- Solar cells and Li-ion battery
- Inertial sensor extension board features:
 - 3-axis gyroscope
 - Pressure and temperature sensor
 - Magnetometer and accelerometer
- Primer2 (STM3210E-PRIMER) and Primer1 (STM3210B-PRIMER) are replaced by the STM32F performance line EvoPrimer.

Table 1. Device summary

Part number	Order code		
	STM3240GPRIMER		
STM32-PRIMER	STM3210GPRIMER ⁽¹⁾		
STW32-PRIMER	STM3210CPRIMER		
	STM32L15PRIMER		
STM8L-PRIMER	STM8L1526PRIMER		
	STM3240GPRIM-D		
	STM3210GPRIM-D ⁽¹⁾		
	STM3210CPRIM-D		
OT 400 450	STM32L15PRIM-D		
STMPRIMER (accessories)	STM8L1526PRIM-D		
	STMPRIMER-PROTO		
	STMPRIMER-BASE		
	STMPRIMER-EXT		

 "STM3210EPRIMER and STM3210EPRIM-D" are replaced by "STM3210GPRIMER and STM3210GPRIM-D" with MCU with 1 Mbyte of Flash instead of 512 Kbytes.

November 2011 Doc ID 13942 Rev 8 1/7

1 Description

Raisonance's Primers are a uniquely fun, easy, low-risk solution for exploring, evaluating and developing applications for the STM32 and STM8 microcontrollers. They include everything that users need to better understand the STM32/STM8's peripheral implementation and operation.

The EvoPrimer range is an enhancement of the original Primer1 and Primer2 devices. It offers even more flexibility to evaluate a range of STM32 microcontrollers and STM8L ultralow power line microcontrollers, using the same EvoPrimer base with interchangeable target boards (to test different microcontrollers) or extension boards.

- The EvoPrimer base has a removable transparent cover and USB cable which includes features such as the debugging/programming interface and most of the hardware features that you need to evaluate the capabilities of the target MCU. The base can also be extended by using its add-on connector to add components and circuitry.
- The EvoPrimer target board(s) include the target MCU and may also include additional hardware features for target MCU evaluation.


The Primers can be purchased as complete evaluation tools, which can then be modified by purchasing an accessory, or they can be created from the interchangeable accessories:

- The complete evaluation tools for the STM8L and STM32 microcontroller families consist of an EvoPrimer base with the relevant EvoPrimer target board.
- The EvoPrimer accessories permit the EvoPrimer base and EvoPrimer target boards (and extension boards) to be ordered separately.

Figure 1. EvoPrimer base



Figure 2. EvoPrimer target boards



2 Primer usage

Power up

If your EvoPrimer base and the target board are not connected, simply insert the target board into the EvoPrimer base, switch on the power switch and slide the transparent cover in place.

Press the joystick to power up the complete EvoPrimer and plug it directly into a host PC's USB port for in-circuit debugging and device programming.

Note:

EvoPrimer bases are charged in the factory to ensure minimum operation upon reception. The battery needs charging as soon as possible via the EvoPrimer base's debug USB port.

Play

Start exploring the power of the STM32/STM8 by playing with the included applications. The base drives the fun, ergonomic hardware platform that combines a TFT graphical display with MEMs-based controls plus a tactile screen and joystick for navigating and controlling the GUI and game applications.

The Primers enable you to discover, edit and fine tune applications using Raisonance's Ride7 software toolset which drives the hardware and offers a full range of project management, source code editing and debugging features from an intuitive GUI.

The Primers can operate in standalone mode powered by a battery with power management circuit which is recharged via the USB connection to a host PC.

When the STM8L or STM32L EvoPrimer target boards are disconnected from the base, they have the unique feature of being able to run off their own battery which is recharged by their solar cells. They can use this feature to operate as a standalone temperature sensor application!

More resources

You can develop applications using sample applications from Raisonance or other engineers at *www.mcu-circle.com* as the starting point for new innovations. All the preloaded sample applications, new applications and the CircleOS task scheduler can be downloaded for free from the mcu-circle web site. This Primer dedicated internet site also provides FAQ, user forums, links to development resources and much more.

Note:

Raisonance's Ride7 supports the complete range of STR7/9, STM32, STM8, ST7 and uPSD 8-bit microcontroller families. For details about available compilers and special features for each family, refer to the STMicroelectronics microcontroller support site on www.st.com.



Doc ID 13942 Rev 8

3 Development software

The **EvoPrimers** require that the most recent version of the following software (for compiling, programming and debugging) is downloaded from the mcu-circle web site:

- Ride7 development software toolset with an intuitive GUI for:
 - Project manager
 - Source code editor
 - High-level language debugger
- A compiler:
 - GNU C/C++ compiler, no code size limitations (STM32)
 - Raisonance C compiler (STM8L)
- CircleOS task scheduler for dynamic loading and management of new applications.
- C source code for all sample applications and libraries including:
 - MEMs (GUI application controls)
 - TFT display (touchscreen, graphical interface, games, bitmap converter)
 - Audio record and playback (Primer2 and EvoPrimers)
- Complete documentation is provided with the software installation.

For more software and ideas, take a look at the dedicated online community and resources at www.stm8circle.com and www.stm32circle.com.

577

4 Ordering information

The Primers are available from the STMicroelectronics sales offices and distributors. For more information and complete documentation please visit www.mcu-circle.com or the STMicroelectronics microcontroller support site www.st.com.

Table 2. Order codes

Order code	Description				
	Base	Target MCU	Flash	Notes	
Complete evaluation tool - includes base + target board					
STM3240GPRIMER	EvoPrimer	STM32F407IG	1MB		
STM3210GPRIMER	EvoPrimer	STM32F103VG	1MB		
STM3210CPRIMER	EvoPrimer	STM32F107VC	256 KB		
STM32L15PRIMER	EvoPrimer	STM32L152VB	128 KB		
STM8L1526PRIMER	EvoPrimer	STM8L152C6	32 KB		
STMPRIMER accessories					
STM3240GPRIM-D	N/A	STM32F407IG	1MB	MCU target board ⁽¹⁾	
STM3210GPRIM-D	N/A	STM32F103VG	1MB	MCU target board ⁽¹⁾	
STM3210CPRIM-D	N/A	STM32F107VC	256 KB	MCU target board ⁽¹⁾	
STM32L15PRIM-D	N/A	STM32L152VB	128 KB	MCU target board ⁽¹⁾	
STM8L1526PRIM-D	N/A	STM8L152C6	32 KB	MCU target board ⁽¹⁾	
STMPRIMER-PROTO	N/A	Prototype	N/A	5 prototyping extension boards ⁽¹⁾	
STMPRIMER-BASE	EvoPrimer	N/A	N/A	EvoPrimer base for use with EvoPrimer MCU target boards and extension boards.	
STMPRIMER-EXT	N/A	N/A	N/A	Inertial sensor extension board ⁽¹⁾	

^{1.} For use with the EvoPrimer base which can be either ordered separately (STMPRIMER-BASE) or be part of an complete evaluation tool.

5 Revision history

Table 3. Document revision history

Date	Revision	Changes	
26-Sep-2007	1	Initial release.	
30-Oct-2008	2	Added the STM3210E-PRIMER details.	
21-Jun-2010	3	Added EvoPrimer details. Removed Primer1 and Primer2 details as they are replaced by the STM32F performance line EvoPrimer.	
15-Jul-2010	4	Changed STM8L-PRIMER order code.	
13-Dec-2010	5	Removed Primer1 and Primer2 as well as STM3210E-PRIMER and STM3210B-PRIMER. Updated <i>Features</i> to mention MCU for STM8L and STM32F EvoPrimer.	
27-Sep-2011	6	Replaced STM3210EPRIMER and STM3210EPRIM-D with STM3210GPRIMER and STM3210GPRIM-D and updated Development software. Updated Table 1 and Table 2.	
07-Nov-2011	7	Added STMPRIMER-EXT in <i>Table 1</i> and <i>Table 2</i> and corresponding features on the cover page. Updated <i>Note 1</i> in <i>Table 2</i> . Renamed STM8L and STM32L EnergyLite devices to STM8L and STM32L utlralow power devices. Updated links to online community and resources in <i>Section 3: Development software</i> .	
29-Nov-2011	8	Added STM3240GPRIMER and STM3240GPRIM-D in <i>Table 1</i> and <i>Table 2</i> . Updated <i>Features</i> to include STM32F high-performance and DSP EvoPrimer features.	

6/7 Doc ID 13942 Rev 8

Please Read Carefully:

Information in this document is provided solely in connection with ST products. STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, modifications or improvements, to this document, and the products and services described herein at any time, without notice.

All ST products are sold pursuant to ST's terms and conditions of sale.

Purchasers are solely responsible for the choice, selection and use of the ST products and services described herein, and ST assumes no liability whatsoever relating to the choice, selection or use of the ST products and services described herein.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted under this document. If any part of this document refers to any third party products or services it shall not be deemed a license grant by ST for the use of such third party products or services, or any intellectual property contained therein or considered as a warranty covering the use in any manner whatsoever of such third party products or services or any intellectual property contained therein.

UNLESS OTHERWISE SET FORTH IN ST'S TERMS AND CONDITIONS OF SALE ST DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY WITH RESPECT TO THE USE AND/OR SALE OF ST PRODUCTS INCLUDING WITHOUT LIMITATION IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION), OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT.

UNLESS EXPRESSLY APPROVED IN WRITING BY TWO AUTHORIZED ST REPRESENTATIVES, ST PRODUCTS ARE NOT RECOMMENDED, AUTHORIZED OR WARRANTED FOR USE IN MILITARY, AIR CRAFT, SPACE, LIFE SAVING, OR LIFE SUSTAINING APPLICATIONS, NOR IN PRODUCTS OR SYSTEMS WHERE FAILURE OR MALFUNCTION MAY RESULT IN PERSONAL INJURY, DEATH, OR SEVERE PROPERTY OR ENVIRONMENTAL DAMAGE. ST PRODUCTS WHICH ARE NOT SPECIFIED AS "AUTOMOTIVE GRADE" MAY ONLY BE USED IN AUTOMOTIVE APPLICATIONS AT USER'S OWN RISK.

Resale of ST products with provisions different from the statements and/or technical features set forth in this document shall immediately void any warranty granted by ST for the ST product or service described herein and shall not create or extend in any manner whatsoever, any liability of ST.

ST and the ST logo are trademarks or registered trademarks of ST in various countries.

Information in this document supersedes and replaces all information previously supplied.

The ST logo is a registered trademark of STMicroelectronics. All other names are the property of their respective owners.

© 2011 STMicroelectronics - All rights reserved

STMicroelectronics group of companies

Australia - Belgium - Brazil - Canada - China - Czech Republic - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan - Malaysia - Malta - Morocco - Philippines - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States of America

www.st.com



Doc ID 13942 Rev 8 7/7