



NOTES:



DIMENSIONS CONFORM WITH JEDEC TO-243C EXCEPT WHERE INDICATED.

2. DIMENSIONS ARE EXPRESSED IN MILLIMETERS(INCHES).

3. DIMENSIONING AND TOLERANCING LAW: ASME Y14.5M

| SYMBOL | MIN | NOM | MAX |
|--------|--------------------|----------------|----------------|
| A | 1.40 (.055) | 1.50 (.059) | 1.60 (.063) |
| B | .44 (.017) | .50 (.020) | .56 (.022) |
| B1 | .36 (.014) | .42 (.0165) | .48 (.019) |
| C | .35 (.014) | .40 (.016) | .44 (.017) |
| D | 4.40 (.173) | 4.50 (.177) | 4.60 (.181) |
| D1 | 1.62 (.064) | 1.73 (.068) | 1.83 (.072) |
| E | 2.29 (.090) | 2.50 (.098) | 2.60 (.102) |
| E1 | 2.13 (.084) | 2.20 (.087) | 2.29 (.090) |
| e | 1.50 BSC (.059) | | |
| e1 | 3.00 BSC (.118) | | |
| H | 3.94 (.155) | 4.10 (.161) | 4.25 (.167) |
| L | .89 (.035) | 1.10 (.043) | 1.20 (.047) |
| M | 2.2 (.087) | 2.40 (.095) | 2.6 (.102) |