http://www.BDTIC.com/SAMSUNG

M372F320(8)0DT1-C EDO Mode

32M x 72 DRAM DIMM with ECC Using 16Mx4, 4K & 8K Refresh, 3.3V

GENERAL DESCRIPTION

The Samsung M372F320(8)0DT1-C is a 32Mx72bits Dynamic RAM high density memory module. The Samsung M372F320(8)0DT1-C consists of thirty-six CMOS 16Mx4bits DRAMs in TSOP 400mil packages and two 16 bits driver IC in TSSOP package mounted on a 168-pin glass-epoxy sub-strate. A 0.1 or 0.22uF decoupling capacitor is mounted on the printed circuit board for each DRAM. The M372F320(8)0DT1-C is a Dual In-line Memory Module and is intended for mounting into 168 pin edge connector sockets.

PERFORMANCE RANGE

Speed	t_{RAC}	t_{CAC}	t_{RC}	t_{HPC}
-C50	50ns	18ns	84ns	20ns
-C60	60ns	20ns	104ns	25ns

FEATURES

- Part Identification

Part number	PKG	Ref.	CBR Ref.	ROR Ref.
M372F3200DT1-C	TSOP	4K	4K/64ms	
M372F3280DT1-C	TSOP	8K	4K/64ms	8K/64ms

- Extended Data Out Mode Operation
- $\overline{CAS}$-before-$\overline{RAS}$ Refresh capability
- $\overline{RAS}$-only and Hidden refresh capability
- LVTTL compatible inputs and outputs
- Single 3.3V±0.3V power supply
- JEDEC standard pinout & Buffered PDpin
- Buffered input except $\overline{RAS}$ and DQ
- PCB : Height(2100mil), double sided component

PIN CONFIGURATIONS

Pin	Front	Pin	Front	Pin	Front	Pin	Back	Pin	Back	Pin	Back
1	Vss	29	*$\overline{CAS2}$	57	DQ22	85	Vss	113	*$\overline{CAS3}$	141	DQ58
2	DQ0	30	$\overline{RAS0}$	58	DQ23	86	DQ36	114	$\overline{RAS1}$	142	DQ59
3	DQ1	31	$\overline{OE0}$	59	Vcc	87	DQ37	115	RFU	143	Vcc
4	DQ2	32	Vss	60	DQ24	88	DQ38	116	Vss	144	DQ60
5	DQ3	33	A0	61	RFU	89	DQ39	117	A1	145	RFU
6	Vcc	34	A2	62	RFU	90	Vcc	118	A3	146	RFU
7	DQ4	35	A4	63	RFU	91	DQ40	119	A5	147	RFU
8	DQ5	36	A6	64	RFU	92	DQ41	120	A7	148	RFU
9	DQ6	37	A8	65	DQ25	93	DQ42	121	A9	149	DQ61
10	DQ7	38	A10	66	DQ26	94	DQ43	122	A11	150	DQ62
11	DQ8	39	A12	67	DQ27	95	DQ44	123	*A13	151	DQ63
12	Vss	40	Vcc	68	Vss	96	Vss	124	Vcc	152	Vss
13	DQ9	41	RFU	69	DQ28	97	DQ45	125	RFU	153	DQ64
14	DQ10	42	RFU	70	DQ29	98	DQ46	126	B0	154	DQ65
15	DQ11	43	Vss	71	DQ30	99	DQ47	127	Vss	155	DQ66
16	DQ12	44	$\overline{OE2}$	72	DQ31	100	DQ48	128	RFU	156	DQ67
17	DQ13	45	$\overline{RAS2}$	73	Vcc	101	DQ49	129	$\overline{RAS3}$	157	Vcc
18	Vcc	46	$\overline{CAS4}$	74	DQ32	102	Vcc	130	$\overline{CAS5}$	158	DQ68
19	DQ14	47	*$\overline{CAS6}$	75	DQ33	103	DQ50	131	*$\overline{CAS7}$	159	DQ69
20	DQ15	48	W2	76	DQ34	104	DQ51	132	PDE	160	DQ70
21	DQ16	49	Vcc	77	DQ35	105	DQ52	133	Vcc	161	DQ71
22	DQ17	50	RSVD	78	Vss	106	DQ53	134	RSVD	162	Vss
23	Vss	51	RSVD	79	PD1	107	Vss	135	RSVD	163	PD2
24	RSVD	52	DQ18	80	PD3	108	RSVD	136	DQ54	164	PD4
25	RSVD	53	DQ19	81	PD5	109	RSVD	137	DQ55	165	PD6
26	Vcc	54	Vss	82	PD7	110	Vcc	138	Vss	166	PD8
27	$\overline{W0}$	55	DQ20	83	ID0	111	RFU	139	DQ56	167	ID1
28	$\overline{CAS0}$	56	DQ21	84	Vcc	112	$\overline{CAS1}$	140	DQ57	168	Vcc

NOTE : A12 is used for only M372F3280DT1-C (8K Ref.)

PIN NAMES

Pin Names	Function
A0, B0, A1 - A11	Address Input(4K ref)
A0, B0, A1 - A12	Address Input(8K ref)
DQ0 - DQ71	Data In/Out
$\overline{W0}$, $\overline{W2}$	Read/Write Enable
$\overline{OE0}$, $\overline{OE2}$	Output Enable
$\overline{RAS0}$ - $\overline{RAS3}$	Row Address Strobe
$\overline{CAS0}$, 1,4,5	Column Address Strobe
Vcc	Power(+3.3V)
Vss	Ground
NC	No Connection
$\overline{PDE}$	Presence Detect Enable
PD1 - 8	Presence Detect
ID0 - 1	ID bit
RSVD	Reserved Use
RFU	Reserved for Future Use

Pins marked '*' are not used in this module.

PD & ID Table

Pin	50NS	60NS
PD1	1	1
PD2	0	0
PD3	0	0
PD4	0	0
PD5	1	1
PD6	0	1
PD7	0	1
PD8	0	0
ID0	0	0
ID1	0	0

PD Note :PD & ID Terminals must each be pulled up through a register to Vcc at the next higher level assembly. PDs will be either open (NC) or driven to Vss via on-board buffer circuits.


ID Note : IDs will be either open (NC) or connected directly to Vss without a buffer.

PD : 0 for Vol of Drive IC & 1 for N.C


ID : 0 for Vss & 1 for N.C


http://www.BDTIC.com/SAMSUNG

FUNCTIONAL BLOCK DIAGRAM



NOTE : A12 is used for only M372F3280DT1 (8K Ref.)





http://www.BDTIC.com/SAMSUNG

ABSOLUTE MAXIMUM RATINGS *

Item	Symbol	Rating	Unit
Voltage on any pin relative V_{SS}	V_{IN}, V_{OUT}	-0.5 to +4.6	V
Voltage on V_{CC} supply relative to V_{SS}	V_{CC}	-0.5 to +4.6	V
Storage Temperature	T_{stg}	-55 to +125	°C
Power Dissipation	P_D	36	W
Short Circuit Output Current	I_{OS}	50	mA

* Permanent device damage may occur if ABSOLUTE MAXIMUM RATINGS are exceeded. Functional operation should be restricted to the conditions as detailed in the operational sections of this data sheet. Exposure to absolute maximum rating conditions for intended periods may affect device reliability.

RECOMMENDED OPERATING CONDITIONS (Voltage referenced to V_{SS}, T_A = 0 to 70°C)

Item	Symbol	Min	Typ	Max	Unit
Supply Voltage	V_{CC}	3.0	3.3	3.6	V
Ground	V_{SS}	0	0	0	V
Input High Voltage	V_{IH}	2.0	-	V_{CC}+0.3[*1]	V
Input Low Voltage	V_{IL}	-0.3[*2]	-	0.8	V

*1 : V_{CC}+1.3V at pulse width≤15ns, which is measured at V_{CC}.
*2 : -1.3V at pulse width≤15ns, which is measured at V_{SS}.

DC AND OPERATING CHARACTERISTICS (Recommended operating conditions unless otherwise noted)

Symbol	Speed	M372F3200DT1		M372F3280DT1		Unit
		Min	Max	Min	Max	
I_{CC1}	-50 -60	- -	1998 1818	- -	1458 1278	mA mA
I_{CC2}	Don't care	-	100	-	100	mA
I_{CC3}	-50 -60	- -	1998 1818	- -	1458 1278	mA mA
I_{CC4}	-50 -60	- -	1638 1458	- -	1638 1458	mA mA
I_{CC5}	Don't care	-	30	-	30	mA
I_{CC6}	-50 -60	- -	1998 1818	- -	1998 1818	mA mA
$I_{I(L)}$ $I_{O(L)}$	Don't care	-10 -10	10 10	-10 -10	10 10	uA uA
V_{OH} V_{OL}	Don't care	2.4 -	- 0.4	2.4 -	- 0.4	V V

I_{CC1}*: Operating Current * ($\overline{RAS}$, $\overline{CAS}$, Address cycling @t_{RC}=min)
I_{CC2} : Standby Current ($\overline{RAS}$=$\overline{CAS}$=$\overline{W}$=V_{IH})
I_{CC3}*: $\overline{RAS}$ Only Refresh Current * ($\overline{CAS}$=V_{IH}, $\overline{RAS}$ cycling @t_{RC}=min)
I_{CC4}*: Extended Data Out Mode Current * ($\overline{RAS}$=V_{IL}, $\overline{CAS}$ cycling : t_{HPC}=min)
I_{CC5} : Standby Current ($\overline{RAS}$=$\overline{CAS}$=$\overline{W}$=Vcc-0.2V)
I_{CC6}*: $\overline{CAS}$-Before-$\overline{RAS}$ Refresh Current * ($\overline{RAS}$ and $\overline{CAS}$ cycling @t_{RC}=min)
$I_{(IL)}$: Input Leakage Current (Any input 0≤V_{IN}≤Vcc+0.3V, all other pins not under test=0 V)
$I_{(OL)}$: Output Leakage Current(Data Out is disabled, 0V≤V_{OUT}≤Vcc)
V_{OH} : Output High Voltage Level (I_{OH} = -2mA)
V_{OL} : Output Low Voltage Level (I_{OL} = 2mA)

*** NOTE** : I_{CC1}, I_{CC3}, I_{CC4} and I_{CC6} are dependent on output loading and cycle rates. Specified values are obtained with the output open. I_{CC} is specified as an average current. In I_{CC1} and I_{CC3}, address can be changed maximum once while $\overline{RAS}$=V_{IL}. In I_{CC4}, address can be changed maximum once within one EDO mode cycle time, t_{HPC}.

http://www.BDTIC.com/SAMSUNG

CAPACITANCE (T_A = 25°C, f = 1MHz)

Item	Symbol	Min	Max	Unit
Input capacitance[A0, B0, A1 - A12]	C_{IN1}	-	20	pF
Input capacitance[W0, W2, OE0, OE2]	C_{IN2}	-	20	pF
Input capacitance[RAS0 - RAS3]	C_{IN3}	-	73	pF
Input capacitance[CAS0, 1,4,5]	C_{IN4}	-	20	pF
Input/Output capacitance[DQ0 - 71]	C_{DQ}	-	24	pF

AC CHARACTERISTICS (0°C≤T_A≤70°C, V_{CC}=3.3V±0.3V. See notes 1,2.)

Test condition : V_{ih}/V_{il}=2.2/0.7V, V_{oh}/V_{ol}=2.0/0.8V, output loading CL=100pF

Parameter	Symbol	-50		-60		Unit	Note
		Min	Max	Min	Max		
Random read or write cycle time	t_{RC}	84		104		ns	
Read-modify-write cycle time	t_{RWC}	128		153		ns	
Access time from RAS	t_{RAC}		50		60	ns	3,4,10
Access time from CAS	t_{CAC}		18		20	ns	3,4,5,13
Access time from column address	t_{AA}		30		35	ns	3,10,13
CAS to output in Low-Z	t_{CLZ}	8		8		ns	3,13
OE to output in Low-Z	t_{OLZ}	8		8		ns	3,13
Output buffer turn-off delay from CAS	t_{CEZ}	8	18	8	18	ns	6,11,13
Transition time(rise and fall)	t_T	1	50	1	50	ns	2
RAS precharge time	t_{RP}	30		40		ns	
RAS pulse width	t_{RAS}	50	10K	60	10K	ns	
RAS hold time	t_{RSH}	13		15		ns	13
CAS hold time	t_{CSH}	36		38		ns	13
CAS pulse width	t_{CAS}	8	10K	10	10K	ns	
RAS to CAS delay time	t_{RCD}	15	32	18	40	ns	4,13
RAS to column address delay time	t_{RAD}	10	20	13	25	ns	10,13
CAS to RAS precharge time	t_{CRP}	10		10		ns	13
Row address set-up time	t_{ASR}	5		5		ns	13
Row address hold time	t_{RAH}	5		8		ns	13
Column address set-up time	t_{ASC}	0		0		ns	
Column address hold time	t_{CAH}	7		10		ns	
Column address to RAS lead time	t_{RAL}	30		35		ns	13
Read command set-up time	t_{RCS}	0		0		ns	
Read command hold referenced to CAS	t_{RCH}	0		0		ns	8
Read command hold referenced to RAS	t_{RRH}	-2		-2		ns	8,13
Write command set-up time	t_{WCS}	0		0		ns	7
Write command hold time	t_{WCH}	7		10		ns	
Write command pulse width	t_{WP}	7		10		ns	
Write command to RAS lead time	t_{RWL}	13		15		ns	13
Write command to CAS lead time	t_{CWL}	7		10		ns	
Data set-up time	t_{DS}	-2		-2		ns	9,13
Data hold time	t_{DH}	13		15		ns	9,13
Refresh period(4K & 8K)	t_{REF}		64		64	ms	
CAS to W delay time	t_{CWD}	33		38		ns	7
RAS to W delay time	t_{RWD}	68		82		ns	7,13

http://www.BDTIC.com/SAMSUNG

AC CHARACTERISTICS (0°C≤TA≤70°C, VCC=3.3V±0.3V. See notes 1,2.)

Parameter	Symbol	-50		-60		Unit	Note
		Min	Max	Min	Max		
Column address to $\overline{W}$ delay time	t_{AWD}	45		53		ns	7
$\overline{CAS}$ precharge time to $\overline{W}$ delay time	t_{CPWD}	47		58		ns	
$\overline{CAS}$ setup time($\overline{CAS}$-before-$\overline{RAS}$ refresh)	t_{CSR}	10		10		ns	13
$\overline{CAS}$ hold time($\overline{CAS}$-before-$\overline{RAS}$ refresh)	t_{CHR}	8		8		ns	13
$\overline{RAS}$ to $\overline{CAS}$ precharge time	t_{RPC}	3		3		ns	13
Access time from $\overline{CAS}$ precharge	t_{CPA}		33		40	ns	3,13
Hyper page cycle time	t_{HPC}	20		25		ns	12
Hyper page read-modify-write cycle time	t_{HPRWC}	70		77		ns	12
$\overline{CAS}$ precharge time(Hyper page cycle)	t_{CP}	7		10		ns	
$\overline{RAS}$ pulse width (Hyper page cycle)	t_{RASP}	50	200K	60	200K	ns	
$\overline{RAS}$ hold time from $\overline{CAS}$ precharge	t_{RHCP}	35		40		ns	13
$\overline{W}$ to $\overline{RAS}$ precharge time(C-B-R refresh)	t_{WRP}	15		15		ns	13
$\overline{W}$ to $\overline{RAS}$ hold time(C-B-R refresh)	t_{WRH}	8		8		ns	13
$\overline{OE}$ access time	t_{OEA}		18		20	ns	13
$\overline{OE}$ to data delay	t_{OED}	15		18		ns	13
Output buffer turn off delay time from $\overline{OE}$	t_{OEZ}	8	18	8	18	ns	13
$\overline{OE}$ command hold time	t_{OEH}	5		5		ns	
Output data hold time($\overline{C}$-B-$\overline{R}$ refresh)	t_{DOH}	10		10		ns	13
Output buffer turn off delay time from $\overline{RAS}$	t_{REZ}	3	13	3	13	ns	6,11
Output buffer turn off delay time from $\overline{W}$	t_{WEZ}	8	18	8	18	ns	6,13
$\overline{W}$ to data delay	t_{WED}	20		20		ns	13
$\overline{OE}$ to $\overline{CAS}$ hold time	t_{OCH}	5		5		ns	
$\overline{CAS}$ hold time to $\overline{OE}$	t_{CHO}	5		5		ns	
$\overline{OE}$ precharge time	t_{OEP}	5		5		ns	
$\overline{W}$ pulse width (Hyper page cycle)	t_{WPE}	5		5		ns	
Present Detect Read Cycle							
$\overline{PDE}$ to Valid PD bit	t_{PD}		10		10	ns	
$\overline{PDE}$ to PD bit Inactive	t_{PDOFF}	2	7	2	7	ns	

http://www.BDTIC.com/SAMSUNG

NOTES

1. An initial pause of 200us is required after power-up followed by any 8 RAS-only or CAS-before-RAS refresh cycles before proper device operation is achieved.

2. Input voltage levels are V_{ih}/V_{il}. V_{IH}(min) and V_{IL}(max) are reference levels for measuring timing of input signals. Transition times are measured between V_{IH}(min) and V_{IL}(max) and are assumed to be 5ns for all inputs.

3. Measured with a load equivalent to 1 TTL loads and 100pF.

4. Operation within the t_{RCD}(max) limit insures that t_{RAC}(max) can be met. t_{RCD}(max) is specified as a reference point only. If t_{RCD} is greater than the specified t_{RCD}(max) limit, then access time is controlled exclusively by t_{CAC}.

5. Assumes tha $t_{RCD} \geq t_{RCD}$(max).

6. This parameter defines the time at which the output achieves the open circuit condition and is not referenced to V_{OH} or V_{OL}.

7. t_{WCS}, t_{RWD}, t_{CWD}, t_{AWD} and t_{CPWD} are not restrictive operating parameter. They are included in the data sheet as electrical characteristics only. If $t_{WCS} \geq t_{WCS}$(min) the cycle is an early write cycle and the data out pin will remain high impedance for the duration of the cycle. If $t_{RWD} \geq t_{RWD}$(min), $t_{CWD} \geq t_{CWD}$(min), $t_{AWD} \geq t_{AWD}$(min) and $t_{CPWD} \geq t_{CPWD}$(min). The cycle is a read-modify-write cycle and the data out will contain data read from the selected cell. If neither of the above sets of conditions is satisfied, the condition of data out(at access time) is indeterminate.

8. Either t_{RCH} or t_{RRH} must be satisfied for a read cycle.

9. These parameters are referenced to the CAS leading edge in early write cycles.

10. Operation within the t_{RAD}(max) limit insures that t_{RAC}(max) can be met. t_{RAD}(max) is specified as reference point only. If t_{RAD} is greater than the specified t_{RAD}(max) limit, then access time is controlled by t_{AA}.


11. If RAS goes high before CAS high going, the open circuit condition of the output is achieved by CAS high going. If CAS goes high before RAS high going , the open circuit condition of the output is achieved by RAS going.

12. $t_{ASC} \geq 6$ns.

13. The timing skew from the DRAM to the DIMM resulted from the addition of buffers.

http://www.BDTIC.com/SAMSUNG


READ CYCLE



http://www.BDTIC.com/SAMSUNG

WRITE CYCLE (EARLY WRITE)


NOTE : DOUT = OPEN



http://www.BDTIC.com/SAMSUNG

WRITE CYCLE ($\overline{OE}$ CONTROLLED WRITE)

NOTE : DOUT = OPEN




Don't care

Undefined


http://www.BDTIC.com/SAMSUNG

READ - MODIFY - WRITE CYCLE



http://www.BDTIC.com/SAMSUNG


HYPER PAGE READ CYCLE



http://www.BDTIC.com/SAMSUNG

HYPER PAGE WRITE CYCLE (EARLY WRITE)

NOTE : DOUT = OPEN




Don't care

Undefined


http://www.BDTIC.com/SAMSUNG

HYPER PAGE READ-MODIFY-WRITE CYCLE



http://www.BDTIC.com/SAMSUNG

HYPER PAGE READ AND WRITE MIXED CYCLE




http://www.BDTIC.com/SAMSUNG

$\overline{RAS}$ - ONLY REFRESH CYCLE*


NOTE : $\overline{W}$, $\overline{OE}$, D_{IN} = Don't care

D_{OUT} = OPEN



$\overline{CAS}$ - BEFORE - $\overline{RAS}$ REFRESH CYCLE


NOTE : $\overline{OE}$, A = Don't care



* In $\overline{RAS}$-only refresh cycle of 64Mb A-dile & B-die, when $\overline{CAS}$ signal transits from Low to High, the valid data may be cut off.

http://www.BDTIC.com/SAMSUNG


HIDDEN REFRESH CYCLE (READ)



http://www.BDTIC.com/SAMSUNG

HIDDEN REFRESH CYCLE (WRITE)

NOTE : DOUT = OPEN




Don't care

Undefined

http://www.BDTIC.com/SAMSUNG

CAS-BEFORE-RAS REFRESH COUNTER TEST CYCLE




NOTE : This timing diagram is applied to all devices besides 64M DRAM based modules.

http://www.BDTIC.com/SAMSUNG


CAS - BEFORE - RAS SELF REFRESH CYCLE

NOTE : OE, A = Don't care



TEST MODE IN CYCLE

NOTE : OE , A = Don't care




Don't care

Undefined


http://www.BDTIC.com/SAMSUNG

PACKAGE DIMENSIONS


Units : Inches (millimeters)



(Front view)



(Back view)



Detail A **Detail B** **Detail C**

Tolerances : ±.005(.13) unless otherwise specified

The used device is 16Mx4 DRAM with EDO mode, TSOP II.
DRAM Part No. : M372F3200DT1 - K4E640412D-T.
M372F3280DT1 - K4E660412D-T.